## **LLM Optimization**

Jordan Boyd-Graber

University of Maryland

Mixture of Experts


Slides adapted from William Fedus and Barret Zoph

#### Motivation

- The trend is to bigger models
- But what if you can do as well with N different models?

#### Motivation

- The trend is to bigger models
- But what if you can do as well with N different models?
- Problem is, how to know which model to use?



#### Motivation

- The trend is to bigger models
- But what if you can do as well with N different models?
- Problem is, how to know which model to use?

#### Getting MoRE out of Mixture of Language Model Reasoning Experts

Chenglei Si<sup>1,4</sup> Weijia Shi<sup>2</sup> Chen Zhao<sup>3</sup>
Luke Zettlemoyer<sup>2</sup> Jordan Boyd-Graber<sup>1</sup>

<sup>1</sup> University of Maryland

<sup>3</sup> NYU Shanghai

Clsi@stanford.edu

Chen Zhao<sup>3</sup>

Jordan Boyd-Graber<sup>1</sup>

<sup>2</sup> University of Washington

<sup>4</sup> Stanford University

## Why is it a good idea?

- If you need a model to do x, easier to train that model than to train a massive model to do everything and x
- Users find it more interpretable
- Disagreements between models can help with calibration
- Cheaper to serve (smaller models can live on modest, smaller servers)

## Why is it a good idea?

- If you need a model to do x, easier to train that model than to train a massive model to do everything and x
- Users find it more interpretable
- Disagreements between models can help with calibration
- Cheaper to serve (smaller models can live on modest, smaller servers)

#### Switch Transformers: Scaling to Trillion Parameter Models with Simple and Efficient Sparsity

#### William Fedus\*

LIAMFEDUS@GOOGLE.COM

#### Barret Zoph\*


BARRETZOPH@GOOGLE.COM


#### Noam Shazeer


NOAM@GOOGLE.COM


Google, Mountain View, CA 94043, USA

Editor: Alexander Clark









### Routing

The router variable  $W_r$  produces logits  $h(x) = W_r \cdot x$  which are normalized via a softmax distribution:

$$p_i(x) = \frac{e^{h(x)_i}}{\sum_{j=0}^{N} e^{h(x)_j}}.$$
 (1)

The top-k gate values are selected for routing the token x to linearly weight each expert's contribution

$$y = \sum_{i \in \mathcal{T}} p_i(x) E_i(x). \tag{2}$$

• Just use same objective?

- Just use same objective?
- Shazeer et al. (2018) and Leipkhin et al. (2020): auxiliary loss
- Given N experts indexed by i = 1 to N and a batch B with T tokens

$$loss = \alpha \cdot N \cdot \sum_{i=1}^{N} f_i \cdot P_i$$
 (3)

where  $f_i$  is the fraction of tokens dispatched to expert i,

- Just use same objective?
- Shazeer et al. (2018) and Leipkhin et al. (2020): auxiliary loss
- Given N experts indexed by i = 1 to N and a batch B with T tokens

$$loss = \alpha \cdot N \cdot \sum_{i=1}^{N} f_i \cdot P_i$$
 (3)

where  $f_i$  is the fraction of tokens dispatched to expert i,

$$f_i = \frac{1}{T} \sum_{x \in \mathcal{R}} \mathbb{1}\{\operatorname{argmax} p(x) = i\}$$
 (4)

and  $P_i$  is the fraction of the router probability allocated for expert i,

- Just use same objective?
- Shazeer et al. (2018) and Leipkhin et al. (2020): auxiliary loss
- Given N experts indexed by i = 1 to N and a batch B with T tokens

$$loss = \alpha \cdot N \cdot \sum_{i=1}^{N} f_i \cdot P_i$$
 (3)

where  $f_i$  is the fraction of tokens dispatched to expert i,

$$f_i = \frac{1}{T} \sum_{x \in \mathcal{R}} \mathbb{1}\{\operatorname{argmax} p(x) = i\}$$
 (4)

and  $P_i$  is the fraction of the router probability allocated for expert i,

$$P_i = \frac{1}{T} \sum_{x \in \mathcal{D}} p_i(x). \tag{5}$$

Since we seek uniform routing of the batch of tokens across the N experts, we desire both vectors to have values of 1/N.

### Why can this help?

- Easier fine tuning (more on this later)
- Increase in overall scale
- Easier to distribute to more machines (Experts on different devices)

#### Wrapup

- Most major models are likely using mixture of experts
- It helps keep training scalable
- And allows to claim larger models
- It also leads to better results
- Helps address sparsity issue: most of models aren't useful for any particular example

