Hypothesis Testing

INST 808: Jordan Boyd-Graber

University of Maryland

Fall 2020

Observ	⁄ed		
	Favor	Indifferent	Oppose
Dem	138	83	64
Rep	64	67	84

Expect	ed		
	Favor	Indifferent	Oppose
Dem			
Rep			

Observ	ed		
	Favor	Indifferent	Oppose
Dem	138	83	64
Rep	64	67	84

Expect	ed		
	Favor	Indifferent	Oppose
Dem	115.14		
Rep			

Obse	rved		
	Favor	Indifferent	Oppose
Dem	138	83	64
Rep	64	67	84

Expect	ed		
	Favor	Indifferent	Oppose
Dem	115.14	85.50	
Rep			

C)bserv	⁄ed		
		Favor	Indifferent	Oppose
	Dem	138	83	64
	Rep	64	67	84

Expect	ed		
	Favor	Indifferent	Oppose
Dem	115.14	85.50	84.36
Rep			

Observ	⁄ed		
	Favor	Indifferent	Oppose
Dem	138	83	64
Rep	64	67	84

	Expect	ea			
		Favor	Indifferent	Oppose	
Ī	Dem	115.14	85.50	84.36	
	Rep	86.86			

Type a steed

Observ	red		
	Favor	Indifferent	Oppose
Dem	138	83	64
Rep	64	67	84

Expect	eu		
	Favor	Indifferent	Oppose
Dem	115.14	85.50	84.36
Rep	86.86	64.50	

Evpected

Observed						
	Favor	Indifferent	Oppose			
Dem	138	83	64			
Rep	64	67	84			

LAPCOICG						
Favor	Indifferent	Oppose				
115.14	85.50	84.36				
86.86	64.50	63.64				
	Favor 115.14	Favor Indifferent 115.14 85.50				

Observed						
	Favor	Indifferent	Oppose			
Dem	138	83	64			
Rep	64	67	84			

Expected						
	Favor	Indifferent	Oppose			
Dem	115.14	85.50	84.36			
Rep	86.86	64.50	63.64			

$$4.539 + 0.073 + 4.914 + 6.016 + 0.097 + 6.514 = 22.152$$
 (1)

Running test: df, p-Value

• Degrees of Freedom?

Running test: df, p-Value

- Degrees of Freedom? $(r-1)(c-1) = 1 \cdot 2 = 2$
- p-value

Running test: df, *p*-Value

- Degrees of Freedom? $(r-1)(c-1) = 1 \cdot 2 = 2$
- p-value

```
>>> from scipy.stats.distributions import chi2
>>> 1 - chi2.cdf(22.15, 2)
1.5494894118783797e-05
>>> from scipy.stats import chisquare
>>> chisquare([138, 83, 64, 64, 67, 84],
... [115.14, 85.5, 84.36, 86.86, 64.5, 63.64],
... 3)
Power_divergenceResult(statistic=22.152468645918482,
```

pvalue=1.5475780213

US vs. Japanese Mileage

Read in Data

4 17 31.0

```
>>> import pandas as pd
>>> mpg = pd.read_csv("jp-us-mpg.dat", delim_whitespace=Tr
>>> mpg.head()
    US    Japan
0    18    24.0
1    15    27.0
2    18    27.0
3    16    25.0
```

First things first

• Compute means

First things first

Compute means

```
>>> from numpy import mean
>>> mean(mpg["Japan"].dropna())
30.481012658227847
>>> mean(mpg["US"].dropna())
20.14457831325301
```

• Compute sample variances

First things first

Compute means

```
>>> from numpy import mean
>>> mean(mpg["Japan"].dropna())
30.481012658227847
>>> mean(mpg["US"].dropna())
20.14457831325301
```

Compute sample variances

```
>>> from numpy import var
>>> us = mpg["US"].dropna()
>>> jp = mpg["Japan"].dropna()
>>> jp_std = std(jp) * len(jp) / float(len(jp) - 1)
>>> us_std = std(us) * len(us) / float(len(us) - 1)
```

- Degrees of freedom:
- · Test statistic:
- p-value

- Degrees of freedom: 79 1 = 78
- · Test statistic:
- p-value

- Degrees of freedom: 79-1=78
- Test statistic: $\frac{30.48-25}{\frac{6.14}{\sqrt{79}}}$
- p-value

- Degrees of freedom: 79-1=78
- Test statistic: $\frac{30.48-25}{\frac{6.14}{\sqrt{79}}}$
- p-value

```
>>> t_test
7.93278589688753
>>> from scipy import stats
>>> 1.0 - stats.t.cdf(abs(t_test), 78)
6.349143433226345e-12
```